

266nm Microchip Laser System of MB Series



DESCRIPTION

MB series microchip laser products have very ideal narrow pulse width, but also can achieve high single pulse energy. The product is a passive Q-switched solid-state laser based on semiconductor pump. The laser pulse is pure and tailless, the single pulse energy is stable, and the beam quality is good. The integrated design of semiconductor pump module and laser crystal makes the compact laser head easy to install and integrate. The system supports internal and external triggering. This series of products include four wavelengths of 1064nm, 532nm, 355nm and 266nm. The full sealing module inside the laser head can be used by customers for secondary development and application. The superior product performance index makes its application range very wide, especially in laser measurement, which can meet many different kinds of measurement needs, and also has excellent performance in the application of laser seeds.


FEATURES

- Pulse energy up to 170μJ
- External pump source fiber pump pulse
- Charge energy up to 360μJ
- Maximum repetition frequency up to 1kHz
- Beam mode is TEM00
- Fully sealed design, high reliability

APPLICATIONS



- Seed source
- Micromachining
- Biomedical Science
- Laser ultrasonic inspection
- Laser ionization mass spectrometry
- Non-linear optical measurement
- Seed source

OUTLINE SIZE(mm)




Main view of Driven

Rear view of Driven



Unit: mm



Top view of Driven



* Optical fiber pump for external pump source, power supply length: 200mm



PARAMETERS

Model	CL266-100Hz-10μJ-MB001	
Optical Parameter	Wavelength (nm)	266
	Repetition Frequency (kHz)	0.1
	Average Power (mW)	1
	Output Energy (uJ)	10
	Pulse Width (ps)	500
	Power Stability (8h)	±3%
	Beam Mode	TEM ₀₀
	Full-Angle Divergence Angle Typ. (Mrad) Level @ 1/e ²	< 2
	Vertical @ 1/e ²	< 2
	Polarization Characteristics	> 100:1
System Parameters	Power Input	100-240 VAC,50/60Hz
	Modulation Input	TTL0-5V,SMA interface
	Control Interface	RS232、USB
	System Power Consumption (W)	< 30
	Power Supply Size (W × H × L, mm)	168×88×140/168×88×220*
	Laser Head Size (W × H × L, mm)	45×30×120
	Working Temperature (°C)	15-35
Storage Temperature (°C)	0-60	

